



### Performance Specifications

- Surge Capacity (L-N, N-G)  
120kA/phase  
160kA/phase
- **UL 1449 Third Edition Testing Completed**
- **UL 1449 Second Edition Revision Listed (UL 1449 Rev '2.5' Listed)**
- UL 1283 Fourth Edition Listed
- UL Listed to Canadian safety standards
- UL 1449 Listed 200kA SCCR
- 200KAIR Rated Fusing
- Less than ½ Nanosecond Response Time
- 5000 Category C3 (C High) Impulses with <10% Drift

### Environmental Specifications

- Relative Humidity Range: 0 - 95% Non-Condensing
- Operating Frequency: 47 - 63 Hz
- Operating Temperature: -40° C (-40° F) to +65° C (+149° F)

### Standard Configuration

- External Mount NEMA 1 Standard Enclosure (Other enclosures available)
- Standard Size: 12" x 12" x 6" (Options may increase Enclosure Size)
- Weight: 25 Lbs.

### Design Features

- Designed, Manufactured, & Tested consistent with:
  - IEEE C62.41.1-2002, C62.41.2-2002, and C62.45-2002
  - ANSI/IEEE C62.41-1991 and C62.45-1992
  - NEMA LS-1
  - NEC 285.6
- Large Block Utility Grade 40mm MOVs
- High Energy Parallel Design for Category C3 applications, the highest exposure to surge activity
- For External Mounting next to Switchgear, Motor Control Centers, or Panelboards
- AC Sinewave Tracking Filter with EMI/RFI
- Filtering up to -50dB from 100kHz to 100MHz
- Individually Fused Suppression Modules
- Thermal Cutout in each Module
- Typical connection: #6 AWG and 30 - 60A Breaker
- Solid State Bi-directional
- Redundant LEDs to Indicate Loss of Protection or Circuit Fully Operational

### Quality

- 10 Year Warranty
- Burn-in Tested Prior to Shipment
- Short Circuit Current Rating 200,000 rms Symmetrical Amperes (UL Listed)
- ISO 9001:2000 Quality Management System

*Suppression elements are encapsulated in UL Listed and Patented Ceramgard®*



**PQ GLOBAL**

7940 Silverton Ave Suite 105 San Diego, CA, 92126  
Tel: 1-858-271-5996 · Fax: 1-858-271-5995  
www.pqglobal.com · info@pqglobal.com



# TE/(x)HPS/(zz)/M

x = Voltage Code, zz = Options

Model	Service Voltage	UL 1449 Suppressed Voltage Rating (SVR)				MCOV
		L-N	L-G	N-G	L-L	
TE/1HPS	240V/120 Split Phase	330		330	700	150
TE/11HPS	120V Single Phase	330		330		150
TE/12HPS	240V Single Phase	600		600		275
TE/2HPS	208Y/120V Three Phase, WYE	330		330	700	150
TE/3HPS	240V/120V Three Phase, High-Leg, DELTA	330/700		330	700/1200	150/275
TE/4HPS	480Y/277V Three Phase, WYE	700		600	1200	320
TE/5HPS	480V Three Phase, DELTA		1500		1500	575
TE/51HPS	480V Three Phase, Corner Grounded, DELTA		1500		1500	575
TE/6HPS	240V Three Phase, DELTA		700		700	275
TE/61HPS	240V Three Phase, Corner Grounded, DELTA		700		700	275
TE/7HPS	380Y/220V Three Phase, WYE	700		600	1200	320
TE/8HPS	600Y/347V Three Phase, WYE	1000		900	1800	420
TE/9HPS	600V Three Phase, DELTA		1500		1800	750
TE/91HPS	600V Three Phase, Corner Grounded, DELTA		1500		1800	750

**Note:** /CL Option Not Available on TE/8, 9, 91

Ordering information for Optional Features should be appended to the model number and separated by a slash(/).  
Example: TE/2HPS/CL/DS/M

### Available Options:

- /CX** Module Option increases the surge current capacity to 120kA/phase
- /CL** Module Option increases the surge current capacity to 160kA/phase
- /DC** The Dry Contacts monitor each phase providing a summary alarm (with the Remote Monitor Option)  
The contacts are terminated in a DB-9 connector
- /RM** Remote Monitor with indicator lights and audible alarm is available for use with the Dry Contact Option
- /FM** Flush Mount Option replaces the standard surface mount enclosure
- /3R** NEMA 3R enclosure - diagnostic display inside enclosure
- /04** NEMA 4 enclosure - diagnostic display inside enclosure
- /4X** NEMA 4X Non-Metallic enclosure - diagnostic display inside enclosure - visible through door
- /4S** NEMA 4X Stainless Steel enclosure - diagnostic display inside enclosure

**PQ GLOBAL**

7940 Silverton Ave Suite 105 San Diego, CA, 92126  
Tel: 1-858-271-5996 · Fax: 1-858-271-5995  
www.pqglobal.com · info@pqglobal.com

